



Brick Tag



MINIATURE TAGS MOUNT OR EMBED DISCREETLY TO TOOLS, EQUIPMENT, MEDICAL INSTRUMENTS AND MORE

- **Small footprints** – Embeddable in space-restricted applications.
- **Exceptional durability** – Withstand physical stress, are dust tight, and resistant to water, chemicals, acids and temperature extremes.
- **Versatility** – Available in LF, HF and UHF; may be customized to fit application requirements.

HID Global Brick Tag passive contactless transponders easily integrate into RFID applications requiring discreet placement of small, featherweight tags that deliver sustainable performance.

smaller formats without compromising performance. The tags provide a full 64-bit UID and 1024-bit user memory, optionally usable for NFC applications.

TECHNOLOGY HIGHLIGHTS:

- Resistant to chemicals, shock and vibration
- Tiny footprints
- Heat resistant
- Waterproof
- LF, HF/NFC, UHF/RAIN options

Brick Tag Ceramic units are optimized for placement on metal assets, such as tools, weaponry and surgical instrumentation. The hard shells encasing these tiny UHF transponders shield them from exposure to autoclave sterilization and demanding industrial environments. Their memory is readable and writable from up to 3.3 ft (1 m).

The epoxy Brick Tag Nova and Brick Tag HDX low frequency transponders are only 0.12 in (3.0 mm) thick. The Nova tag's 160-bit read-write memory is easily programmed to suit custom applications. The HDX version is read-only, and meets ISO 11784 and ISO 11785 standards. Both withstand extreme temperatures, and provide high water, chemical and shock resistance. Widely used in key fobs for automobile immobilizer theft prevention systems, these devices are also ideal for tool or cable inventory and tracking systems.

The Brick Tag ABS Vigo™ transponder is among the smallest HF tags available. These units are assembled using patented DBond™ Vigo™ technology that enables HID Global to produce tags in thinner,

APPLICATION AREAS:

- **Asset tracking and logistics**
 - Cable identification
 - Tool or weapon inventory and management
 - Key fobs for automobile immobilization systems
- **Medical and health**
 - Surgical instrumentation tracking
 - Medical equipment status and utilization

SPECIFICATIONS

	Brick Tag								
	Epoxy		ABS	Ceramic					
	Nova	HDX	Vigo	60	75	150	600	60	
Base Model Number	933504	9B7513	6A9904	698936 (EU) 698937 (US)	698930 (EU) 698931 (US)	698932 (EU) 698933 (US)	698934 (EU) 698935 (US)	6H2936 (EU) 6H2937 (US)	
ELECTRONIC									
Operating Frequency	130 kHz	134.2 kHz	13.56 MHz	865-868 MHz (ETSI) / 902-928 MHz (FCC)					
Chip Type	Nova	HDX	Vigo	Higgs 3				Monza R6-P	
Memory	160 bit EEPROM	128 bit read-only	64 bit UID, 1024 bit EEPROM	512 bit read/write				28/96 bit EPC, 32/64 bit UM	
Anti-Collision				Yes					
Reading Distance	Proximity			4.9 ft (1.5 m)	6.5 ft (2 m)	13 ft (4 m)	22.9 ft (7 m)	6.5 ft (2 m)	
PHYSICAL									
Dimensions	0.5 × 0.2 × 0.1 in (12 × 6 × 3 mm)		0.4 × 0.1 × 0.1 in (10 × 3 × 2.5 mm)	0.4 × 0.1 × 0.1 in (10 × 2.5 × 2.5 mm)	0.2 × 0.2 × 0.1 in (5 × 5 × 3 mm)	0.4 × 0.2 × 0.1 in (10 × 5 × 3 mm)	0.9 × 0.4 × 0.1 in (23 × 9 × 3 mm)	0.4 × 0.1 × 0.1 in (10 × 2.6 × 2.6 mm)	
Mounting Method	Enclose			Adhesive or enclosure					
Affixes to	Any material			Metal surfaces					
Housing Material	Epoxy overmolded		ABS coffin potted w/ epoxy	Ceramic painted					
Color	Black			Black					
Weight	0.02 oz (0.45 g)		0.005 oz (0.15 g)	0.01 oz (0.4 g)		0.03 oz (0.9 g)	0.11 oz (3.2 g)	0.01 oz (0.4 g)	
CHEMICAL AND MECHANICAL RESISTANCE									
Water	IP68, 68° F (20° C), 1 m × 24 h			IP67, 1 m × 1 h					
Withstands Exposure To	Bleach, caustic soda, formic acid, gasoline, HCL, oil, salt water			Autoclave sterilization; bleach, cleaning solutions, oil					
Environmental Test Conditions	68° F (20° C), 100 h								
Axial / Radial Force	500 N, 10 sec								
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]								
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]								
Drop Test	100 × 1 m								
Pressure	100 bar, 5 min								
THERMAL									
Storage	-40° to +248° F (-40° to +120° C), 1 × 1000 h		-13° to +158° F (-25° to +70° C), 1 × 1000 h	-40° to +185° F (-40° to +85° C)					
Operating	-40° to +194° F (-40° to +90° C)		-13° to +158° F (-25° to +70° C)	-40° to +185° F (-40° to +85° C)					
Shock/Fatigue	-40° to +194° F (-40° to +90° C), 200 × 20 min with 30 sec transition		-13° to +158° F (-25° to +70° C), 200 × 5 min with 30 sec transition	-40° to +185° F (-40° to +85° C)					
Peak Temperature	284° F (140° C), 100 h			302° F (150° C), 100 h					
OTHER									
Standards	ISO 11784, 11785		ISO 15693, 18000-3, NFC Tag Type 5 when NDEF formatted	EPC C1G2, ISO 18000-6C, RAIN					
Options	Alternative LF or HF integrated chips			Self-adhesive sticker					
Quantity Per Box	500 pcs.		4,000 pcs.	4,000 pcs	10,000 pcs	4,000 pcs	2,000 pcs	4,000 pcs	
Warranty	2 years								



hidglobal.com



North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 9171 1108

© 2019-2020 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and Brick Tag Vigo are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
2020-08-21-hid-rfid-il-brick-tag-ds-en PLT-00271

An ASSA ABLOY Group brand

ASSA ABLOY